

# Flat single-axis photovoltaic support main beam

What are the dynamic characteristics of photovoltaic support systems?

Key findings are as follows. Dynamic characteristics of tracking photovoltaic support systems obtained through field modal testing at various inclinations, revealing three torsional modes within the 2.9-5.0 Hz frequency range, accompanied by relatively small modal damping ratios ranging from 1.07 % to 2.99 %.

What are the dynamic characteristics of the tracking photovoltaic support system?

Through processing and analyzing the measured modal data of the tracking photovoltaic support system with Donghua software, the dynamic characteristic parameters of the tracking photovoltaic support system could be obtained, including frequencies, vibration modes and damping ratio.

What is a finite element model of tracking photovoltaic support system?

Finite element model of tracking photovoltaic support system. The tracking photovoltaic support system consisted of 10 pillars (including 1 drive pillar), one axis bar, 11 shaft rods, 52 photovoltaic panels, 54 photovoltaic support purlins, driving devices and 9 sliding bearings, and also includes the connection between the frame and its axis bar.

Does tracking photovoltaic support system have a modal analysis?

While significant progress has been made by scholars in the exploration of wind pressure distribution, pulsation characteristics, and dynamic response of tracking photovoltaic support system, there is a notable gap in the literature when it comes to modal analysis of tracking photovoltaic support system.

How many pillars does a photovoltaic support system have?

The tracking photovoltaic support system consisted of 10 pillars (including 1 drive pillar), one axis bar, 11 shaft rods, 52 photovoltaic panels, 54 photovoltaic support purlins, driving devices and 9 sliding bearings, and also includes the connection between the frame and its axis bar. Total length was 60.49 m, as shown in Fig. 8.

How stiff is a tracking photovoltaic support system?

Because the support structure of the tracking photovoltaic support system has a long extension length and the components are D-shaped hollow steel pipes, the overall stiffness of the structure was found to be low, and the first three natural frequencies were between 2.934 and 4.921.



# Flat single-axis photovoltaic support main beam

Contact us for free full report

Web: <https://publishers-right.eu/contact-us/>

Email: [energystorage2000@gmail.com](mailto:energystorage2000@gmail.com)

WhatsApp: 8613816583346

